

# THE M-SERIES TUBE EXPANDER DRIVE

## Pneumatic Torque Controlled Motors

The M-Series Pneumatic torque controlled rolling motor, is an incredibly effective and productive machine.

Easily managed by a single operator, featuring simple set up, and control procedures. Controlled through a roller throttle you can change from forward to reverse at the flick of a wrist.

Light in weight the machine is also less tiring to use that some other hand held rolling machines.

### Features

- Three Sizes ¾", 1" , 1 ¼"
- Roll throttle Forward and Reverse
- Torque Adjustable
- Robustly Built
- Quick Change Chuck
- Ready to Use
- Complete with Tool Box, Spare set of paddles and Instruction Manual
- Economically Priced



### TECHNICAL SPECIFICATION

MODEL	TUBE SIZE	FREE SPEED	MAX TORQUE		MIN TORQUE		LENGTH		WEIGHT		CHUCK SIZE
			In.lbs	Nm	In.lbs	Nm	Ins	mm	Lbs	Kg	
M19-1250	¾"	1250	110	12.25	12	1.35	10	255	9.4	4.25	3/8"
M25-700	1"	700	210	23.70	20	2.26	10	255	9.9	4.50	3/8"
M32-500	1 ¼"	500	319	36.00	44	5.00	10	255	11.0	5.00	3/8"

### WICKSTEED ENGINEERING LIMITED

Hove Road, Rushden, Northamptonshire NN10 0JB • Tel: +44 (0)1933 318555 • Fax: +44 (0)1933 410103 • Email: mail@wicksteed.com  
www.wicksteed.com